

Package: RClimacell (via r-universe)

October 9, 2024

Title R Wrapper for the 'Climacell' API

Version 0.1.4

Description 'Climacell' is a weather platform that provides hyper-local forecasts and weather data. This package enables the user to query the core layers of the time line interface of the 'Climacell' v4 API <<https://www.climacell.co/weather-api/>>. This package requires a valid API key. See vignettes for instructions on use.

License MIT + file LICENSE

URL <https://nikdata.github.io/RClimacell/>

BugReports <https://github.com/nikdata/RClimacell/issues>

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

Imports dplyr (>= 1.0.0), magrittr (>= 2.0.1), stringr (>= 1.4.0), tibble (>= 3.0.6), httr (>= 1.4.2), lubridate (>= 1.7.9.2), rlang (>= 0.4.10), tidyr (>= 1.1.2), assertthat (>= 0.2.1), tidyselect

Suggests knitr, rmarkdown

VignetteBuilder knitr

Depends R (>= 2.10)

Repository <https://nikdata.r-universe.dev>

RemoteUrl <https://github.com/nikdata/rclimacell>

RemoteRef HEAD

RemoteSha 33689a72f150c8c1292f1449e143c560c086fa42

Contents

climacell_celestial	2
climacell_core	3
climacell_precip	4
climacell_temperature	6
climacell_wind	7
dict_moonphase	9
dict_preciptype	9
dict_weathercode	9

Index	10
--------------	-----------

climacell_celestial	<i>Sunrise, Sunset, and Moon Phase Readings from Climacell</i>
---------------------	--

Description

This function will make a call to the Climacell API and retrieve sunrise, sunset times and moon phase variables.

Usage

```
climacell_celestial(
  api_key,
  lat,
  long,
  timestep = "1d",
  start_time = NULL,
  end_time = NULL
)
```

Arguments

api_key	character string representing the private API key. Provided by user or loaded automatically from environment variable (environment variable must be called "CLIMACELL_API").
lat	a numeric value (or a string that can be coerced to numeric) representing the latitude of the location.
long	a numeric value (or a string that can be coerced to numeric) representing the longitude of the location.
timestep	a 'step' value for the time. For the climacell_celestial function, the only acceptable value (per the limitations of the Climacell API) is '1d'.
start_time	the start time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. It is recommended that the lubridate::now() function or Sys.time() be used to define the start_time.

For this function, the `start_time` cannot be less than 6 hours from the current time.

`end_time` the end time of the query. This input must be a character string that can be parsed into a `data/time` or a `date/time` value. If the input does not contain a timezone, the value will be assumed to be in UTC. For this function, the `end_time` cannot be greater than 15 days from the current date/time.

Details

`climacell_celestial` returns a tibble that consists of sunrise/sunset times along with the moon phase (code & description).

Value

a tibble

Examples

```
## Not run:
climacell_celestial(
  api_key = Sys.getenv('CLIMACELL_API'),
  lat = 0,
  long = 0,
  timestep = '1d',
  start_time = lubridate::now(),
  end_time = lubridate::now() + lubridate::days(5))

## End(Not run)
```

climacell_core	<i>Climacell Core Layer Data</i>
----------------	----------------------------------

Description

`climacell_core` returns a tibble that contains all of the Core Layer data from the Climacell version 4 API using the Timelines interface. The intent of this function is to retrieve all of the Core Layer data in a single API call. This is especially handy when using the free API as it limits the usage of the API based on hourly rate and daily usage.

Usage

```
climacell_core(
  api_key,
  lat,
  long,
  timestep,
  start_time = NULL,
  end_time = NULL
)
```

Arguments

api_key	character string representing the private API key. Provided by user or loaded automatically from environment variable (environment variable must be called "CLIMACELL_API").
lat	a numeric value (or a string that can be coerced to numeric) representing the latitude of the location.
long	a numeric value (or a string that can be coerced to numeric) representing the longitude of the location.
timestep	a 'step' value for the time. Choose one of the following valid values: c('1d', '1h', '30m', '15m', '5m', '1m', 'current').
start_time	the start time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. It is recommended that the lubridate::now() function or Sys.time() be used to define the start_time. For this function, the start_time cannot be less than 6 hours from the current time.
end_time	the end time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. OPTIONAL if timestep is 'current' or if the user desires to get the maximum results possible (depends on the timestep chosen).

Value

a tibble

Examples

```
## Not run:
climacell_core(
  api_key = Sys.getenv('CLIMACELL_API'),
  lat = 0,
  long = 0,
  timestep = '1d',
  start_time = lubridate::now(),
  end_time = lubridate::now + lubridate::days(5))

## End(Not run)
```

climacell_precip

Precipitation Readings from Climacell

Description

This function will make a call to the Climacell API and retrieve precipitation related (including cloud cover & pressure) values.

Usage

```
climacell_precip(
  api_key,
  lat,
  long,
  timestep,
  start_time = NULL,
  end_time = NULL
)
```

Arguments

<code>api_key</code>	character string representing the private API key. Provided by user or loaded automatically from environment variable (environment variable must be called "CLIMACELL_API").
<code>lat</code>	a numeric value (or a string that can be coerced to numeric) representing the latitude of the location.
<code>long</code>	a numeric value (or a string that can be coerced to numeric) representing the longitude of the location.
<code>timestep</code>	a 'step' value for the time. Choose one of the following valid values: c('1d', '1h', '30m', '15m', '5m', '1m', 'current').
<code>start_time</code>	the start time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. It is recommended that the <code>lubridate::now()</code> function or <code>Sys.time()</code> be used to define the <code>start_time</code> . For this function, the <code>start_time</code> cannot be less than 6 hours from the current time.
<code>end_time</code>	the end time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. OPTIONAL if timestep is 'current' or if the user desires to get the maximum results possible (depends on the timestep chosen).

Details

`climacell_precip` returns a tibble that consists of precipitation related variables (returned values are in metric units) using the Climacell API. These variables consist of precipitation intensity, precipitation probability, precipitation description, visibility, surface & sea level pressure, cloud cover & ceiling, and a weather description.

Value

a tibble

Examples

```
## Not run:
```

```

climacell_precip(
  api_key = Sys.getenv('CLIMACELL_API'),
  lat = 0,
  long = 0,
  timestep = 'current')

## End(Not run)

```

climacell_temperature *Temperature Readings from Climacell*

Description

This function will make a call to the Climacell API and retrieve temperature related variables.

Usage

```

climacell_temperature(
  api_key,
  lat,
  long,
  timestep,
  start_time = NULL,
  end_time = NULL
)

```

Arguments

api_key	character string representing the private API key. Provided by user or loaded automatically from environment variable (environment variable must be called "CLIMACELL_API").
lat	a numeric value (or a string that can be coerced to numeric) representing the latitude of the location.
long	a numeric value (or a string that can be coerced to numeric) representing the longitude of the location.
timestep	a 'step' value for the time. Choose one of the following valid values: c('1d', '1h', '30m', '15m', '5m', '1m', 'current').
start_time	the start time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. It is recommended that the lubridate::now() function or Sys.time() be used to define the start_time. For this function, the start_time cannot be less than 6 hours from the current time.

`end_time` the end time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. OPTIONAL if timestep is 'current' or if the user desires to get the maximum results possible (depends on the timestep chosen).

Details

`climacell_temperature` returns a tibble that consists of temperature related variables (returned values are in metric units) using the Climacell API. These variables consist of temperature, a "feels like" temperature, dewpoint, and humidity.

Value

a tibble

Examples

```
## Not run:
climacell_temperature(
  api_key = Sys.getenv('CLIMACELL_API'),
  lat = 0,
  long = 0,
  timestep = 'current')

## End(Not run)
```

<code>climacell_wind</code>	<i>Wind Readings from Climacell</i>
-----------------------------	-------------------------------------

Description

This function will make a call to the Climacell API and retrieve wind related variables.

Usage

```
climacell_wind(
  api_key,
  lat,
  long,
  timestep,
  start_time = NULL,
  end_time = NULL
)
```

Arguments

api_key	character string representing the private API key. Provided by user or loaded automatically from environment variable (environment variable must be called "CLIMACELL_API").
lat	a numeric value (or a string that can be coerced to numeric) representing the latitude of the location.
long	a numeric value (or a string that can be coerced to numeric) representing the longitude of the location.
timestep	a 'step' value for the time. Choose one of the following valid values: c('1d', '1h', '30m', '15m', '5m', '1m', 'current').
start_time	the start time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. It is recommended that the lubridate::now() function or Sys.time() be used to define the start_time. For this function, the start_time cannot be less than 6 hours from the current time.
end_time	the end time of the query. This input must be a character string that can be parsed into a data/time or a date/time value. If the input does not contain a timezone, the value will be assumed to be in UTC. OPTIONAL if timestep is 'current' or if the user desires to get the maximum results possible (depends on the timestep chosen).

Details

climacell_wind returns a tibble that consists of wind related variables (returned values are in metric units) using the Climacell API. These variables consist of wind speed, wind gust, and wind direction.

Value

a tibble

Examples

```
## Not run:
climacell_wind(
  api_key = Sys.getenv('CLIMACELL_API'),
  lat = 0,
  long = 0,
  timestep = 'current')

## End(Not run)
```

dict_moonphase	<i>Moonphase Dictionary</i>
----------------	-----------------------------

Description

this is a helper function that returns the moon phase tibble containing the moon phase codes (which are returned by Climacell API) and their appropriate description.

Usage

```
dict_moonphase()
```

Value

a tibble

dict_preciptype	<i>Precipitation Type Dictionary</i>
-----------------	--------------------------------------

Description

this is a helper function that returns the precipitation type tibble containing the precipitation type codes (which are returned by Climacell API) and their appropriate description.

Usage

```
dict_preciptype()
```

Value

a tibble

dict_weathercode	<i>Weather Dictionary</i>
------------------	---------------------------

Description

this is a helper function that returns the weather code tibble containing the weather codes (which are returned by Climacell API) and their appropriate description.

Usage

```
dict_weathercode()
```

Value

a tibble

Index

climacell_celestial, [2](#)
climacell_core, [3](#)
climacell_precip, [4](#)
climacell_temperature, [6](#)
climacell_wind, [7](#)

dict_moonphase, [9](#)
dict_preciptype, [9](#)
dict_weathercode, [9](#)